

BUPI - CLEANER STANDARD-CLEANING MACHINE TWIN TANK - CLEANING MACHINE IN LIFT DOOR VERSION



TECHNICAL DATA:	DB 2 HP	DB 3 HP	DB 4 HP	DB 5 HP	DB 7 HP	Type
Overall Width:	1830	2000	2270	2650	3150	mm
Overall Depth:	1675	1845	2190	2650	3415	mm
Overall Height:	1975	2040	2040	2260	2405	mm
Height with open door:	2510	2630	2660	3160	3360	mm
Loading Height:	971	971	979	979	1078	mm
Usable Interior Height:	640	700	700	900	900	mm
Grate Basket Square:	720	820	1020	1280	1540	mm
Grate Basket Diameter:	871	1012	1295	1663	2111	mm
Grate Basket Rim Height:	200	200	200	200	200	mm
Payload:	500	700	900	1200	1200	kg
Overall Weight:	870	1150	1350	1650	2470	kg
POWER SUPPLY:						
Three phase (alternating current)	400	400	400	400	400	V
Frequency:	50	50	50	50	50	Hz
Control voltage:	230	230	230	230	230	V
Total load:	20,75	26,75	41,75	47,75	88,75	kW
Corresponds to the directions:	ÖVE/VDE	ÖVE/VDE	ÖVE/VDE	ÖVE/VDE	ÖVE/VDE	
SPRAY SYSTEM - WASH/ RINSE						
Spray Pressure - Wash / Rinse	4,2 / 2,5	4,0 / 2,5	4,5 / 2,6	4,1 / 2,9	4,9 / 3,0	bar
PUMP DATA:						
Circulation - Wash/ Rinse	14,0 / 12,9	22,0 / 14,0	28,0/ 16,0	32,0/ 20,0	46,0 / 30,0	m³/h
Water Column H. - Wash / Rinse	47,5 / 30,0	45,0 / 30,5	51,1 / 36,0	46,0 / 34,5	54,5 / 35,5	mWS
Pump Motor - Wash / Rinse	5,5 / 3,0	5,5 / 3,0	7,5 / 4,0	7,5 / 4,0	11,0 / 5,5	kW
ELECTRICAL HEATING						
Tank Contents - Wash / Rinse	200 / 200	250 / 250	350 / 350	500 / 450	800 / 800	litre
Electrical Heaters:	6 / 6	9 / 9	15 / 15	18 / 18	36 / 36	kW
Thermostat Setting:	70 / 70	70 / 70	70 / 70	70 / 70	70 / 70	°C
Heat - Up Time:	1,5 - 2 h	1,5 - 2	1,5 - 2	1,5 - 2	1,5 - 2	hours
VARNISH:	RAL 6011	RAL 6011	RAL 6011	RAL 6011	RAL 6011	

TECHNICAL DATA SUBJECT TO CHANGE WITHOUT NOTICE

BUPI (UNITED KINDOM) LTD.

P.O. BOX 217
GB-LONDON, SW3 2EQ

TEL. 0171 - 486 5353
FAX 01428 - 722080